

3-10K

SOLARATOR SERIES

Works with a Wide Range of Batteries: Experience Uninterrupted Power, Even in Areas with Grid Instability

S6-EH1P(3-8)K-L-PLUS S6-EH1P10K-L-PLUS(21A)

Single Phase | Low Voltage



- Supports PV input up to 160% of the inverter's rated DC power, maximising solar utilisation
- Supports up to 21A PV input current, compatible with future higher-power PV modules
- 200% overload for 10s in off-grid mode, ensuring stable startup of motors, water pumps and air conditioners
- Seamless on/off-grid switching in under 10ms, guaranteeing an uninterrupted power supply
- More battery options, compatible with any battery (between 40V-60V)
- Supports existing PV grid-tied power connection for export control and off-grid use
- Multiple methods of generator connection and auto control, enabling flexible local deployment
- Support max 6 units in parallel, expanding system capacity
- Smart Load management, extending backup time for critical loads
- Customizable battery backup level for uninterrupted power
- Supports PV-only off-grid operation, reducing upfront costs
- AI-Powered & VPP-Ready - maximise savings, unlock additional income
- 7-inch industrial-grade LCD screen, providing a larger, user-friendly interface for local operation
- Ingress protection IP66, for operation in harsh conditions

UK

t: +44 113 328 0870 (sales) e: europesales@solisinverters.com w: solisinverters.com/uk
+44 1514 536515 (service) ukservice@solisinverters.com



DATASHEET

Models	3K	3.6K	5K	6K	8K	10K(21A)	
Input DC (PV side)							
Recommended max. PV array size	6 kW	7.2 kW	10 kW	12 kW	16 kW	20 kW	
Max. usable PV input power	4.8 kW	5.76 kW	8 kW	9.6 kW	12.8 kW	16 kW	
Max. input voltage	500 V						
Rated voltage	330 V						
Start-up voltage	90 V						
MPPT voltage range	90 - 435 V						
Max. input current	16 A / 16 A			32 A / 32 A		42 A / 42 A	
Max. current per DC input	16 A						
Max. short circuit current	20 A / 20 A			40 A / 40 A		48 A / 48 A	
MPPT number / Max. input strings number	2 / 2			2 / 4			
Battery							
Battery type	Li-ion / Lead-acid						
Battery voltage range	40 - 60 V						
Max. charge / discharge power	3 kW	3.6 kW	5 kW	6 kW	8 kW	10 kW	
Max. charge / discharge current	70 A	80 A	112 A	135 A	190 A	210 A	
Number of battery port / number of BMS port	1 / 1						
Communication	CAN / RS485						
Output AC (Grid side)							
Rated output power	3 kW	3.6 kW	5 kW	6 kW	8 kW	10 kW	
Max. apparent output power	3 kVA	3.6 kVA	5 kVA	6 kVA	8 kVA	10 kVA	
Rated grid voltage	L/N/PE, 220 V / 230 V						
Rated grid frequency	50 Hz / 60 Hz						
Rated grid output current	13.7 A / 13.1 A	16.4 A / 15.7 A	22.8 A / 21.8 A	27.3 A / 26.1 A	36.4 A / 34.8 A	45.5 A / 43.5 A	
Power factor	> 0.99 (0.8 leading - 0.8 lagging)						
THDi	< 3%						
Input AC (Grid side)							
Input voltage range	187 - 253 V						
Max. input current	21 A	25 A	32 A	40 A	50 A	65 A	
Output AC (Back-up)							
Rated output power	3 kW	3.6 kW	5 kW	6 kW	8 kW	10 kW	
Max. apparent output power	2 times of rated power, 10 s						
Back-up switch time	< 10 ms						
Rated output voltage	L/N/PE, 220 V / 230 V						
Rated frequency	50 Hz / 60 Hz						
Rated output current	13.7 A / 13.1 A	16.4 A / 15.7 A	22.8 A / 21.8 A	27.3 A / 26.1 A	36.4 A / 34.8 A	45.5 A / 43.5 A	
Max. AC passthrough current	35 A	35 A	40 A	40 A	50 A	65 A	
THDv (@linear load)	< 2%						
Input AC (Generator side)							
Max. input power	3 kW	3.6 kW	5 kW	6 kW	8 kW	10 kW	
Rated input current	13.7 A / 13.1 A	16.4 A / 15.7 A	22.8 A / 21.8 A	27.3 A / 26.1 A	36.4 A / 34.8 A	45.5 A / 43.5 A	
Rated input voltage	1/N/PE, 220 V / 230 V						
Rated input frequency	50 Hz / 60 Hz						
Efficiency							
Max. efficiency	96.2%						
EU efficiency	96.1%						
BAT charged by PV / AC max. efficiency	95.3% / 93.9%						
Battery discharged efficiency	93.8%						
Protection							
Output over current protection	Yes						
Insulation resistance monitoring	Yes						
Residual current detection	Yes						
Integrated PV switch	Yes						
DC reverse-polarity protection	Yes						
Protection class / Over voltage category	I / II (PV and BAT), III (MAINS and BACKUP and GEN)						
Integrated AFCI 2.0	Optional						
Anti-islanding protection	Yes						
General Data							
Dimensions (W × H × D)	335 × 560 × 253 mm						
Weight	23 kg			23.5 kg		23.8 kg	
Topology	Non-isolated (PV), Isolated (Battery)						
Self-consumption	< 40 W						
Operating ambient temperature range	-25 ~ +60°C						
Relative humidity	0 - 100%						
Ingress protection	IP66						
Noise emission (typical)	< 40 dB(A)				< 65 dB(A)		
Cooling concept	Natural cooling				Intelligent redundant fan-cooling		
Max. operation altitude	3000 m						
Grid connection standard	NRS 097-2-1, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, EN 50549-1, MEA, PEA, NBR 16149, NBR 16150, G98, G99, CEI 0-21, NTS 631 TypeA						
Safety / EMC standard	IEC/EN 62109-1/-2, EN 61000-6-2/-3						
Features							
PV connection	MC4 connector						
Battery connection	Terminal Block						
AC connection	Terminal Block						
Display	7.0" LCD display & Bluetooth + APP						
Communication interface	Standard: WIFI+LAN+Bluetooth, CAN-BMS, CAN-Parallelx2, RS485-Meter, RS485, DRM, DI, DOx2; Optional: 2G/3G/4G						