



# THREE-PHASE HYBRID INVERTER



## DATASHEET

SYNK-8K-SG04LP3  
SYNK-10K-SG04LP3  
SYNK-12K-SG04LP3

[www.sunsynk.com](http://www.sunsynk.com)  
[sales@sunsynk.com](mailto:sales@sunsynk.com)  
[customerservices@sunsynk.com](mailto:customerservices@sunsynk.com)

Model	SYNK-8K-SG04LP3	SYNK-10K-SG04LP3	SYNK-12K-SG04LP3
<b>Battery Input Data</b>			
Battery Type	Lead-acid or Li-Ion		
Battery Voltage Range	40Vd.c ~ 60Vd.c		
Max. Charging/Discharging Current	190Ad.c (max.)	210Ad.c (max.)	240Ad.c (max.)
Charging Curve	3 Stages / Equalization		
External Temperature Sensor	Yes		
Charging Strategy for Li-Ion Battery	Self-adaption to BMS		
<b>PV String Input Data</b>			
Max. DC Input Power	10400W	13000W	15600W
PV Input Voltage	550Vd.c (160Vd.c ~ 800Vd.c)		
MPPT Range	200Vd.c ~ 650Vd.c		
Start-up Voltage	160V		
PV Input Current	13Ad.c + 13Ad.c	26Ad.c + 13Ad.c	
Max. PV Isc	17Ad.c + 17Ad.c	34Ad.c + 17Ad.c	
No. of MPPT Trackers	2		
No. of Strings Per MPPT Tracker	1+1	2+1	
<b>AC Output Data</b>			
Rated AC Output and UPS Power	8000W	10000W	12000W
Max. AC Output Power	8800W	11000W	13200W
Peak Power (Off-Grid)	2 times of rated power, 10 S		
AC Output Rated Current	12.1/11.6A	15.2/14.5A	18.2/17.4A
Max. AC Current	13.4/12.8A	16.7/15.9A	20/19.1A
Max. Three-phase Unbalanced Output Current	18.2/17.4A	22.7/21.7A	27.3/26.1A
Max. Output Short Circuit Current	75A		
Max. Continuous AC Passthrough	45A		
Output Frequency and Voltage	50/60Hz;3L/N/PE 220/380, 230/400Vac (Three phase)		
Grid Type	Three phase		
Total Harmonic Distortion (THD)	<3% (of nominal power)		
DC Current Injection	<0.5% In		
<b>Efficiency</b>			
Max. Efficiency	97.60%		
Euro Efficiency	97.00%		
MPPT Efficiency	>99%		
<b>Protection</b>			
Integrated	DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Terminal Insulation Impedance Monitoring, DC Component Monitoring, Overvoltage Load Drop Protection, Ground Fault Current Monitoring, Arc Fault Circuit Interrupter (optional), Power Network Monitoring, Island Protection Monitoring, Earth Fault Detection, DC Input Switch, DC Terminal Insulation Impedance Monitoring, Residual Current (RCD) Detection		
Surge Protection	TYPE II(DC), TYPE II(AC)		
Over Voltage Category	OVC II(DC), OVC III(AC)		

## Certifications and Standards

Grid Regulation	EN 50549-1, AS-NZS 4777.2, NRS 097-2-1; Additional connections available upon request
EMC/Safety Regulation	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2

## General Data

Operating Temperature Range	-40 to +60 °C, >45 °C Derating
Cooling	Intelligent Air Cooling
Noise	≤45 dB
Communication with BMS	RS485; CAN
Net Weight	38.5kg
Gross Weight	47.5kg
Cabinet Size	422W×702H×281D mm (Excluding connectors and brackets)
Protection Degree	IP65
Protective Class	Class I
Inverter Topolgy	Non-Isolated
Installation Style	Wall-mounted
Warranty	5 Years
Pollution degree	PD2 (Inside) PD3 (Outside)
Manufacturer Country	China



### NOTICE

#### Safe Transport and Handling of the Inverter

When transporting the equipment, always use its original packaging and keep it intact as a complete unit. Store the product in a dry environment, avoiding direct sunlight, and maintain a temperature range between -40°C and 60°C. As the equipment can be quite heavy, always consider its total weight when moving, transporting, or installing it, ensuring that the installation site has adequate load-bearing capacity. Transporting and installing the inverter should only be carried out by qualified personnel.



## Contact Us

---

**Call** +44 151 832 4300 **Email** [sales@sunsynk.com](mailto:sales@sunsynk.com) **Website** [www.sunsynk.com](http://www.sunsynk.com)

- Address**
- HK** Room 702-704, 7/F Texwood Plaza, 6 How Ming Street, Kwun Tong, Kowloon, Hong Kong
  - UK** Sunsynk UK Ltd, 17 Turnstone Business Park, Mulberry Avenue, Widnes, Cheshire, WA8 0WN
  - SA** Unit 2, 3 & 4, 80 Highview Blvd, Ferndale, Randburg, 2160, South Africa
  - NL** Sunsynk NL BV, Henri Wijnmalenweg 8, 5657 EP Eindhoven, Netherlands
  - AU** Level 1, 982-988 Wellington Street, West Perth WA 6005, Australia
  - ES** Tafetana, 32 P.I. Las Andoriñas 38639 Las Chafiras Santa Cruz de Tenerife
  - US** 100 S. Ashley Drive, Suite 600, Tampa, Florida, 33602, United States of America